




JVC TO CAMLINX HEAD CABLE




OUTSIDE VIEW



OUTSIDE VIEW



INSIDE VIEW



INSIDE VIEW

LENGTH 350mm

ITEM 1

PIN 1 BROWN _____ TO _____
 PIN 2 RED _____ TO _____
 PIN 3 ORANGE _____ TO _____
 PIN 4 YELLOW _____ TO _____ 1k Resistor _____ TO _____
 PIN 5 GREEN _____ TO _____

ITEM 2

PIN 3
 PIN 3
 PIN 3
 PIN 1 YELLOW
 PIN 4 GREEN

PARTS REQUIRED

ITEM

- 1 6 PIN MINI DIN CABLE. FARNELL 395030
- 2 12 PIN HIROSE FREE PLUG HR10A-10P-10P(73)
- 3 1K RESISTOR 1%
- 4 1.6MM HEATSHRINK SLEEVE. FARNELL 100-8440
- 5 7/0.2 GREY WIRE. FARNELL 121-9332

NOTES.

SLEEVE ALL SOLDER JOINTS WITH 1.6mm HEATSHRINK SLEEVE
 CUT THE MINI TO LENGTH. THIS WILL MAKE 2 CABLES.

ON THE HIROSE THE BRAID IS TO BE FOLDED BACK UNDER THE
 STRAIN RELIEF SO IT MAKES CONTACT WITH THE SHELL.

DRWN	CHCD	APP	DATE	ISS
SJH			21-11-12	A

VOLAMP LTD	
DRG NO	TITLE
CAB-CAMLINX-JVC	HEAD CABLE