




PANASONIC TO CAMLINX HEAD CABLE




OUTSIDE VIEW



OUTSIDE VIEW



INSIDE VIEW



INSIDE VIEW

LENGTH 350mm

ITEM 1

PIN 1 GREEN _____ TO _____
 PIN 2 RED _____ TO _____
 PIN 3 SCREEN _____ TO _____
 PIN 4 YELLOW _____ TO _____
 PIN 5 BLUE _____ TO _____

ITEM 2

PIN 1 GREEN _____
 PIN 2 RED _____
 PIN 5 & 10 SCREEN _____
 PIN 3 YELLOW _____
 PIN 4 BLUE _____

PARTS REQUIRED

ITEM

- 1 12 PIN HIROSE FREE PLUG HR10A-10P-10P(73)
- 2 10 PIN HIROSE FREE PLUG HR10A-10P-10P(73)
- 3 6 CORE SCREENED CABLE.
CUT LENGTH 350mm. FARNELL 119-0259
- 4 1.6MM HEATSHRINK SLEEVE. FARNELL 100-8440
- 5 7/0.2 GREY WIRE. FARNELL 121-9332

NOTES.

SLEEVE ALL SOLDER JOINTS WITH 1.6mm HEATSHRINK SLEEVE

CONNECT SCREEN ON CABLE TO PINS USING 7/0.2 GREY WIRE

THE BRAID IS TO BE FOLDED BACK UNDER THE STRAIN RELIEF SO IT MAKES CONTACT WITH THE SHELL.

DRWN	CHCD	APP	DATE	ISS
SJH			21-11-12	A

VOLAMP LTD	
DRG NO	TITLE
CAB-CAMLINX-PANA	HEAD CABLE